

PRODUCT INFORMATION

DSG FLUID

Description

DSG Fluid is a high performance automatic transmission fluid, which was developed for the latest generation of Double Clutch Transmission.

DSG Fluid is recommended for Audi- and VW-Double Clutch Transmission (DSG), that the ATF oil with No. TL 521 82 needs.

Benefits

- Extremely high wear resistance.
- Excellent viscosity-temperature behavior.
- Foamless, even under difficult conditions.
- Optimum friction characteristics.
- Neutral to metals and sealing materials.
- Low pour point.
- High thermal stability.
- High oxidation stability.
- High load-carrying capacity.

Specification/Recommendations

- ◆ Audi / Volkswagen / Seat / Skoda - G 052 182 A2/A6 (TL 52 182), G 052 529 A2/A6 (TL 52 529)- G 055 529 (TL 52 529-C)
- ◆ BMW - DCTF-1 (83 220 440 214), MTF-LT-5 (83 22 2167 666), 83 22 0397 244, 83 22 2147 477, 83 22 2 148 578, 83 22 2 148 579 und 83 22 2 446 673
- ◆ Volvo Powershift 6-Speed (GFT)/1161838/1161839
- ◆ Ford/Nissan Powershift 6-Speed (GFT), Ford - WSS-M2C-936-A, WSS-M2C-200-D2
- ◆ Chrysler Powershift 6-Speed (Getrag), 68044345 EA & GA
- ◆ Mercedes Benz - MB 236.25, MB 236.21, MB 236,24
- ◆ Citroen / Peugeot- 6DCT451 (PSA 9734.S2)
- ◆ Mitsubishi - Diamond Queen SSTF-1, TC-SST 6-Speed (GFT)
- ◆ Porsche - 043 207 29, 043 207 30, 000 043 20, 000 043 305 13, 999 917 080 00
- ◆ Bugatti Veyron
- ◆ Ferrari - TF DCT-F3
- ◆ Renault EDC 6-Speed (Getrag)
- ◆ Renault - BOT 450
- ◆ ZF TE-ML 11 (ZF004743)
- ◆ Porsche - 000 043 210 44, 971 094 307 02A



Typical Values	Method	Unit	DSG Fluid
Density at 15°C	DIN 51 757	kg/m ³	847
Viscosity at 40°C	DIN 51 562	mm ² /s	36
Viscosity at 100°C	DIN 51 562	mm ² /s	7
Viscosity Index	DIN ISO 2909		158
Dynamic Viscosity at -40°C	DIN 51 938	mPa.s	<18.000
Pour point	DIN ISO 3016	°C	-45
Flash point COC	DIN ISO 2592	°C	>200

Our information is based on thorough research and maybe consider reliable, although not legally binding. The operating instruction and oil recommendation of vehicle and engine manufacturers must be followed.

VOLUME

1 ltr

4 tr

5 ltr

20 ltr

60 ltr

208 ltr

PACKAGING

1 Box
12 Pcs

1 Box
4 Pcs

1 Box
3 Pcs

1 Pc
Can

1 Pc
Drum

1 Pc
Drum