

## PRODUCT INFORMATION

# PREMIUM SYNTHETIC 0W-20

## Description

**Premium Synthetic 0W-20** is a fully synthetic low friction oil to be used in passenger cars gasoline and diesel engines. The special formulation assures maximum thermal and mechanical stability, excellent viscosity temperature dependency and low evaporation loss. The low friction properties of the used synthetic base stocks provide in conjunction with the most modern antifriction additives noticeable reduction of fuel consumption and thus for protection of environment by decreasing pollution.

## Benefits

- The compatibility with elastomers, used in engines, is assured.
- Grants maximum wear protection and features best low temperature properties.
- These assure fast oil provision at all lubrication areas and minimize cold starting wear.
- Highly effective dispersant additives prevent sludge built-up in the oil circuit and deposits on piston and inlets valves.



## Specification/Recommendations

- ◆ ACEA C5
- ◆ Porsche C20
- ◆ API SN PLUS
- ◆ VW-Norm 508 00 and 509 00
- ◆ VW TL 52577

The product is not backwards compatible with VW 504 00 / 507 00 or other VW specifications.

Typical Values	Method	Unit	Premium Synthetic 0W-20
Density at 15°C	DIN 51 757	kg/m <sup>3</sup>	836
Viscosity at 100°C	DIN 51 562	mm <sup>2</sup> /s	8.1
Viscosity at -35°C(ccs)	DIN 51 562	mm <sup>2</sup> /s	3980
Pour point	DIN ISO 3016	°C	-54
Flash point	DIN ISO 2592	°C	234
TBN	DIN ISO 3771	mg KOH/g	8.0

Our information is based on thorough research and maybe consider reliable, although not legally binding. The operating instruction and oil recommendation of vehicle and engine manufacturers must be followed.

<b>VOLUME</b>	1 ltr	4 tr	5 ltr	20 ltr	60 ltr	208 ltr
<b>PACKAGING</b>	1 Box 12 Pcs	1 Box 4 Pcs	1 Box 3 Pcs	1 Pc Can	1 Pc Drum	1 Pc Drum