

## PRODUCT INFORMATION

# PREMIUM SYNTHETIC 5W-40

## Description

**Premium Synthetic 5W-40** is a high performance fully synthetic low friction oil, which is designed for all gasoline and diesel engines of passenger cars, and which especially can be used for fuel injected and turbo charged engines. It is blended from high quality synthetic base oils and selected additives. This makes for a lubricant quality which fulfills and exceeds all requirements of modern passenger car engines.

## Benefits

- Excellent cold start and fast oil feed even at temperatures down to lower than -30°C assure fuel and oil economy.
- Optimized high temperature viscosity to meet latest requirements leads to low oil-caused emissions.
- High wear and corrosion protection and a very good dispersancy provide for an excellent cleanliness of the engine and for long motor life.
- All seasons use by outstanding temperature-viscosity properties and reliable performance reserves even at long drain intervals.

## Specification/Recommendations

- ◆ ACEA A3 / B4
- ◆ API SN / CF
- ◆ BMW LL 98
- ◆ PSA B71 2296
- ◆ Porsche A40
- ◆ Opel GM-LL-B-025
- ◆ Fiat 9.55535-M2
- ◆ VW 502 00 / 505 00
- ◆ MB-Approval 229.3
- ◆ Renault RN 0710 / 0700



Typical Values	Method	Unit	Premium Synthetic 5W-40
Density at 15°C	DIN 51 757	kg/m <sup>3</sup>	853
Viscosity at 100°C	DIN 51 562		14.5
Viscosity index	DIN ISO 2909	mPa.s	170
CCS at -30°C	DIN 51 377	°C	6500
Pour point	DIN ISO 3016	mPa.s	-42
Flash point	DIN ISO 2592	°C	226
TBN	DIN ISO 3771	mg KOH/g	10.3

Our information is based on thorough research and maybe consider reliable, although not legally binding. The operating instruction and oil recommendation of vehicle and engine manufacturers must be followed.

### VOLUME

1 ltr

4 tr

5 ltr

20 ltr

60 ltr

208 ltr

### PACKAGING

1 Box  
12 Pcs

1 Box  
4 Pcs

1 Box  
3 Pcs

1 Pc  
Can

1 Pc  
Drum

1 Pc  
Drum