

PREMIUM SYNTHETIC API SN 15W-40

Description

Premium Synthetic 15W-40 is a high performance low friction oil to be used in passenger cars gasoline and diesel engines. It is produced by blending high quality synthetic oils and mineral base stocks and additives of most progressive technology. Suitable also under severe operating conditions in modern passenger car engines, turbo- or non-turbo charged, and for vans , too.

Benefits

- Improved deposit protection.
- Better wear protection.
- Better low-temperature performance over the life of the oil.
- Its optimized formulation provides lowered fuel- and oil consumption.
- Because of its extended viscosity range the all seasons use is possible.
- This leads to improved motor cleanliness and at least to an extended motor life.
- A special booster raises the quality level up to API SN, which provides improved oxidation resistance.



Specification/Recommendations

◆ ACEA A3 / B4
◆ API SN

◆ MB 229.1

Typical Values	Method	Unit	Premium Synthetic 15W-40
Density at 15°C	DIN 51 757	kg/m ³	864
Viscosity at 40°C	DIN 51 562	mm ² /s	97.8
Viscosity at 100°C	DIN 51 562	mm ² /s	14.6
Viscosity index	DIN ISO 2909		154
CCS at -25°C	DIN 51 377	mPa.s	3430
Pour point	DIN ISO 3016	°C	-45
Flash point	DIN ISO 2592	°C	234
TBN	DIN ISO 3771	mg KOH/g	10.8

Our information is based on thorough research and maybe consider reliable, although not legally binding. The operating instruction and oil recommendation of vehicle and engine manufacturers must be followed.

VOLUME

1 ltr

4 tr

5 ltr

20 ltr

60 ltr

208 ltr

PACKAGING

1 Box
12 Pcs

1 Box
4 Pcs

1 Box
3 Pcs

1 Pc
Can

1 Pc
Drum

1 Pc
Drum