

PRODUCT INFORMATION

SPECIAL HC TURBO 0W-40

Description

Special HC Turbo 0W-40 is a high performance low friction oil for gasoline- and diesel-engines of passenger cars. It is made from highest quality base oils of the synthesis technology. Special long-term protection additives provide enduring motor cleanliness, prevent deposits even at critical motor components, and contribute clearly to a long motor life. Not to be sneezed at the contribution to environmental protection, which is given by the outstanding low friction properties, by the fuel economy of which the CO₂ -emission is reduced.

Benefits

- Suits gasoline- and diesel engines.
- Shows outstanding wear protection properties.
- Provides optimal long term protection for all engines.
- Assures quick oiling even at very high and low temperatures.
- Deploys increased possible savings in fuel consumption.
- Reduces the CO₂ -emission.



Specification/Recommendations

◆ ACEA A3 - / B4 - 12

◆ API SN / CF

Typical Values	Method	Unit	Special HC Turbo 0W-40
Density at 15°C	DIN 51 757	kg/m ³	845
Viscosity at 40°C	DIN 51 562	mm ² /s	75
Viscosity at 100°C	DIN 51 562	mm ² /s	13.8
Viscosity index	DIN ISO 2909		176
Dynamic Viscosity at -35°C	DIN 51 377	mPa.s	5750
Pour point	DIN ISO 3016	°C	-45
Flash point	DIN ISO 2592	°C	226

Our information is based on thorough research and maybe consider reliable, although not legally binding. The operating instruction and oil recommendation of vehicle and engine manufacturers must be followed.

VOLUME

1 ltr

4 tr

5 ltr

20 ltr

60 ltr

208 ltr

PACKAGING

1 Box
12 Pcs

1 Box
4 Pcs

1 Box
3 Pcs

1 Pc
Can

1 Pc
Drum

1 Pc
Drum