

PRODUCT INFORMATION

SPECIAL SYNTHETIC MB 5W-30

Description

Special Synthetic MB 5W-30 is a modern low friction oil with an advanced performance, providing excellent wear protection and above-average cleaning power. It contributes to the service life extension of exhaust-aftertreatment systems and redounds to their trouble-free operation.

Special Synthetic MB 5W-30 is produced on base of the highest quality components, which are currently available. The product is completely compatible with the newest diesel particulate filters (DPF) and with catalytic converters of gasoline engines. It combines outstanding performance with excellent motor protection and improves the reduction of fuel consumption. This oil is recommended for all modern motor cars, especially for high power Otto- and diesel engines in the newest models of passenger cars, sports cars and light commercial vehicles.

Benefits

- Reduction of deposits and sludge by effective cleaning additives.
- Trouble-free cold-starting behaviour by very good low temperature properties.
- Extended oil drain intervals, because of decelerated oil aging by outstanding thermic stability.
- Contribution in the reduction of particle built-up on the diesel particulate filter by its low ash content.
- Reduction of the danger of poisoning on catalytic converters of gasoline engines by its low sulphur and low phosphorus amounts.

Specification/Recommendations

- ◆ ACEA C3
- ◆ GM Dexos 2
- ◆ API SN
- ◆ Porsche C 30
- ◆ MB approval 229.51
- ◆ BMW Longlife-04
- ◆ VW 504 00 / 507 00

Typical Values	Method	Unit	Special Synthetic MB 5W-30
Density at 15°C	DIN 51 757	kg/m ³	850
Viscosity at 40°C	DIN 51 562	mm ² /s	70.8
Viscosity at 100°C	DIN 51 562	mm ² /s	11.8
Viscosity index	DIN ISO 2909		163
CCS at -30°C	DIN 51 377	mPa.s	6080
HTTS at 150°C	ASTM D4683	mPa.s	3.52
Pour point	DIN ISO 3016	°C	-45
Flash point	DIN ISO 2592	°C	230
TBN	DIN ISO 3771	mg KOH/g	8

Our information is based on thorough research and maybe consider reliable, although not legally binding. The operating instruction and oil recommendation of vehicle and engine manufacturers must be followed.



VOLUME

1 ltr

4 tr

5 ltr

20 ltr

60 ltr

208 ltr

PACKAGING

1 Box
12 Pcs

1 Box
4 Pcs

1 Box
3 Pcs

1 Pc
Can

1 Pc
Drum

1 Pc
Drum