

PRODUCT INFORMATION

SUPER CLEAN SYNTECH PREMIUM SAE 10W-40

Description

Super Clean Syntech Premium SAE 10W-40 is a high performance semi-synthetic low friction oil to be used in passenger cars gasoline and diesel engines. It is produced by blending high quality synthetic oils and mineral base stocks and additives of most progressive technology. Suitable also under severe operating conditions in modern passenger car engines, turbo or non turbo charged, and for vans , too.

Super Clean Syntech Premium SAE 10W-40 by its optimized formulation provides lowered fuel and oil consumption. Because of its extended viscosity range the all seasons use is possible. A special booster raises the quality level up to API SN, which provides improved oxidation resistance, improved deposit protection, better wear protection, and better low-temperature performance over the life of the oil. This leads to an improved motor cleanliness and at least to an extended motor life.



Specification/Recommendations

- ◆ ACEA A3 / B4
- ◆ MB 229.3 (covers MB 229.1)
- ◆ API SN
- ◆ VW 501 01 / 505 00
- ◆ Renault RN 700
- ◆ PSA B71 2296

Typical Values	Method	Unit	Super Clean Syntech Premium SAE 10W-40
Density at 15°C	DIN 51 757	kg/m ³	860
Viscosity at 40°C	DIN 51 562	mm ² /s	93.3
Viscosity at 100°C	DIN 51 562	mm ² /s	14.6
Viscosity index	DIN ISO 2909		163
CCS at -25°C	DIN 51 377	mPa.s	5370
Pour point	DIN ISO 3016	°C	-42
Flash point	DIN ISO 2592	°C	232
TBN	DIN ISO 3771	mg KOH/g	10.6

Our information is based on thorough research and maybe consider reliable, although not legally binding. The operating instruction and oil recommendation of vehicle and engine manufacturers must be followed.

VOLUME	1 ltr	4 tr	5 ltr	20 ltr	60 ltr	208 ltr
--------	-------	------	-------	--------	--------	---------

PACKAGING	1 Box 12 Pcs	1 Box 4 Pcs	1 Box 3 Pcs	1 Pc Can	1 Pc Drum	1 Pc Drum
-----------	-----------------	----------------	----------------	-------------	--------------	--------------