

PRODUCT INFORMATION

SUPER FUEL SAVER 5W-30

Description

Super Fuel Saver 5W-30 is a high performance fuel economy oil made from synthetic base oils. It is foreseen for the all-seasons use in passenger cars most modern gasoline- and diesel-engines, even with unit-injector.

Benefits

- Low sulphur-, phosphorus- and ash-content reduce poisoning of catalysators in gasoline engines and decrease the built-up of particles in the diesel particulate filter (DPF) and assist thus the environmental protection by lower pollution.
- Novel high performance additivation assures optimal wear protection and best motor cleanliness.
- Excellent thermal oxidation stability reduces oil aging and allows longer drain intervals at maximum motor protection.
- Best low temperature properties enable unproblematic cold-start of the motor and contribute decisively to a longer operating life of the engine by rapid oil circulation.



Specification/Recommendations

- ◆ ACEA C3
- ◆ API SN-Plus, SN / CF
- ◆ Renault RN 0700 / 0710
- ◆ MB-Approval 229.52
- ◆ VW 502 00 / 505 00 / 505 01 (PD).
- ◆ OV0401547
- ◆ GM Dexos 2
- ◆ MB 226.5
- ◆ BMW LongLife-04
- ◆ MB-Approval 229.51 (covers 229.31)

Typical Values	Method	Unit	Super Fuel Saver 5W-30
Density at 15°C	DIN 51 757	kg/m ³	853
Viscosity at 40°C	DIN 51 562	mm ² /s	67.1
Viscosity at 100°C	DIN 51 562	mm ² /s	11.8
Viscosity index	DIN ISO 2909		173
CCS at -30°C	DIN 51 377	mPa.s	5070
Pour point	DIN ISO 3016	°C	-42
Flash point	DIN ISO 2592	°C	230

Our information is based on thorough research and maybe consider reliable, although not legally binding. The operating instruction and oil recommendation of vehicle and engine manufacturers must be followed.

VOLUME	1 ltr	4 tr	5 ltr	20 ltr	60 ltr	208 ltr
PACKAGING	1 Box 12 Pcs	1 Box 4 Pcs	1 Box 3 Pcs	1 Pc Can	1 Pc Drum	1 Pc Drum