

PRODUCT INFORMATION

SUPER RACE 10W-60 F1

Description

Super Race 10W-60 is a fully synthetic fuel economy oil for all hightech racing engines. It may be used in passenger cars gasoline and diesel engines, and here especially for modern performance-enhanced turbo charged and fuel injected engines. It is very well recommended for the use in motor-cycles with 4-stroke engines on the road as well as off-road.

Benefits

- Holds capacity reserves even at high motor loadings.
- Benefits from the combination of high quality synthetic oils with specially optimized additives.
- Its expanded viscosity range gives additional security, even at continuous maximum load of the engine.

Application

Super Race 10W-60 provides excellent cold-starting properties. Due to the fast oil distribution the motor is effectively protected against cold-starting wear. Furthermore special additive components care for maximum wear protection under all service conditions. Optimal piston cleanliness and prevention of sludge built-up in the stagnant motor go without saying. The image of a high quality motor lubricant is completed by the fuel economy properties, which cause distinctly reduced fuel consumption.

Specification/Recommendations

◆ ACEA A3 / B4

◆ API SN / CF



Typical Values	Method	Unit	Super Race 10W-60 F1
Density at 15°C	DIN 51 757	kg/m ³	859
Viscosity at 40°C	DIN 51 562	mm ² /s	180
Viscosity at 100°C	DIN 51 562	mm ² /s	25.8
Viscosity index	DIN ISO 2909		180
CCS at -25°C	DIN 51 377	mPa.s	5410
Pour point	DIN ISO 3016	°C	-42
Flash point	DIN ISO 2592	°C	226
TBN	DIN ISO 3771	mg KOH/g	13.6

Our information is based on thorough research and maybe consider reliable, although not legally binding. The operating instruction and oil recommendation of vehicle and engine manufacturers must be followed.

VOLUME

1ltr

4 tr

5ltr

20ltr

60ltr

208ltr

PACKAGING

1 Box
12 Pcs

1 Box
4 Pcs

1 Box
3 Pcs

1 Pc
Can

1 Pc
Drum

1 Pc
Drum